

# PICUSQ

PICOSECOND LASER FOR QUANTUM DOT EXCITATION

The **PICUS Q** is housed in a standard 19" enclosure and is made for easy integration into your setup / device.

Fiber-coupled outputs allow flexible pulse delivery offside an optical table. The **PICUS Q** is based on Refined`s proprietary fiber technology that has proven its hands-off performance and stability in biomedical research labs around the world.



- 770 980 nm
- Comfortable fiber delivery
- Optional secondary output up to 1550nm

## EFFICIENT QUANTUM DOT PUMPING

- Repetition rate of 40 MHz
- Narrowband filtered output available

# **ULTRA STABLE**

- Pulse to pulse coherence > 98 % visibility
- Active center wavelength stabilization

# **Applications**

Quantum dot pumping Single-photon sources Material sciences

# **Product Specifications**

**Optical** 

Tuning range	770-980 nm
Pulse to pulse coherence	>98%visibility
Average power	>50mW/>25mW with filter option
Repetition rate	40 +- 0.5 MHz center / +-100 kHz during tuning
Pulse duration	7 - 15 ps
Spectral bandwidth	Typ.1nm; Optionally custom filtering down to 0.1nm
Output fiber	PM780
Polarization	linear, 100:1

### **Electrical**

Interfaces	Communication through USB or RS232 Clock/Reprate out for external synchronisation
Software interfaces	GUI and custom serial API, e.g., via Python & Matlab

### Mechanical

Laser head dimension	44x49x13 cm³
Laser controller dimension	44x45x13 cm³
Cooling	Air-cooled
Weight	15 kg leaser head / 20kg electronics
Standard umbilical length	1.8 m, 10 cm bending radius

# Optional features (specifications preliminary)

Additional filtered output

Filter tuning range	75nm, centered around wavelength of choice
Filter bandwidth	down to 0.1 nm, gaussian shape, independent offset
Filter accuracy	0.01nmresolution; repeatability +- 0.01nm
Filtered output power	bandwidth dependent; typically >1.5 mW for 0.1nm

Additional NIR - (Idler) output

Tuning range	1130 nm to >1500 nm
Output power	typically 20 - 75mW
Spectral bandwidth	<1nm,typically 0.3 nm
Pulse duration	7-15 ps

info@refined-lasers.com www.refined-lasers.com



Refined Laser Systems GmbH Mendelstrasse 11 48149 Münster Germany

The product is constantly being improved, therefore the specifications are subject to change without notice. Aug. 2025 Rev. 5

